

SoudaSeal Metalbond**1. Identification of the substance/preparation and of the company/undertaking**

- 1.1 Identification of the substance or preparation:
Productname: SoudaSeal Metalbond
- 1.2 Use of the substance or the preparation:
Sealant
Adhesive
- 1.3 Company/undertaking identification:
SODAL N.V.
Everdongenlaan 18-20
B-2300 Turnhout
Tel. : +32 14 42 42 31
Fax : +32 14 44 39 71
- 1.4 Telephone number for emergency:
+32 14 58 45 45
Brandweerinformatiecentrum voor gevaarlijke stoffen (B.I.G.)
Technische Schoolstraat 43 A, B-2440 Geel

2. Composition/information on ingredients

Hazardous ingredients	CAS No. EINECS No.	Conc. in %	Hazard symbol	Risks (R-phrases)
trimethoxyvinylsilane	2768-02-7 220-449-8	1 - <10	Xn	10-20-65 (1)
dibutylbis(pentane-2,4-dionato-O,O') tin	22673-19-4 245-152-0	0.1 - <1	Xn;N	36/38-48/22-51/53 (1)

(1) For R-phrases in full: see heading 16

3. Hazards identification

- No hazard classification according to Directive 67/548/EEC and 1999/45/EC

4. First aid measures

- 4.1 Eye contact:
- Rinse immediately with plenty of water
- Seek medical advice
- 4.2 Skin contact:
- Rinse immediately with plenty of water
- If irritation persists: seek medical advice
- 4.3 After inhalation:
- Remove the victim into fresh air
- Seek medical advice
- 4.4 After ingestion:
- Never give water to an unconscious person
- Do not induce vomiting
- Seek medical advice

Printing date : 04-2007
Compiled by : Brandweerinformatiecentrum voor Gevaarlijke Stoffen vzw (BIG)
Technische Schoolstraat 43 A, B-2440 Geel
+32 14 58 45 47 http://www.big.be E-mail: info@big.be

1/8

MSDS established : 27-03-2007
Reference number : BIG\44981GB
Reason for revision : -
Revision date : -
Revision number : 000

SoudaSeal Metalbond

5. Fire-fighting measures

- 5.1 **Suitable extinguishing media:**
- Water spray
 - Polyvalent foam
 - ABC powder
 - Carbon dioxide
- 5.2 **Unsuitable extinguishing media:**
- None
- 5.3 **Special exposure hazards:**
- On burning: release of carbon monoxide, carbon dioxide and formation of small quantities of nitrous vapours
- 5.4 **Instructions:**
- No specific firefighting instructions required
- 5.5 **Special protective equipment for firefighters:**
- Heat/fire exposure: compressed air/oxygen apparatus

6. Accidental release measures

- 6.1 **Personal protection/precautions:**
- See heading 8.2/13
- 6.2 **Environmental precautions:**
- Use appropriate containment to avoid environmental contamination
- 6.3 **Methods of cleaning up:**
- Solid spill: shovel in(to) closing drums
 - Clean contaminated surfaces with a soap solution
 - Wash clothing and equipment after handling

7. Handling and storage

- 7.1 **Handling:**
- Observe normal hygiene standards
- 7.2 **Storage:**
- Store in a dry area
 - Keep away from: heat sources, water/moisture
- | | | | |
|--------------------------------|---|-----------------|------|
| Storage temperature | : | Roomtemperature | |
| Quantity limit | : | N.D. | kg |
| Storage life | : | 365 | days |
| Materials for packaging | : | | |
| - suitable | : | plastic | |
- 7.3 **Specific uses:**
- See information supplied by the manufacturer

8. Exposure controls/Personal protection

8.1 Exposure limit values:

TLV-TWA	:	not listed
TLV-STEL	:	not listed
TLV-Ceiling	:	not listed
WEL-LTEL	:	not listed
WEL-STEL	:	not listed
MAK	:	not listed
MAC-TGG 8 h	:	not listed
MAC-TGG 15 min.	:	not listed
MAC-Ceiling	:	not listed
VME-8 h	:	not listed
VLE-15 min.	:	not listed
GWBB-8 h	:	not listed
GWK-15 min.	:	not listed
Momentary value	:	not listed
EC	:	not listed
EC-STEL	:	not listed

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Work under local exhaust/ventilation

8.2.1.1 Respiratory protection:

- Respiratory protection not required in normal conditions

8.2.1.2 Hand protection:

- Gloves

8.2.1.3 Eye protection:

- Safety glasses

8.2.1.4 Skin protection:

- Protective clothing

8.2.2 Environmental exposure controls: see heading 13

SoudaSeal Metalbond

9. Physical and chemical properties

9.1	General Information:		
	Appearance (at 20°C)	:	Paste
	Odour	:	Characteristic
	Colour	:	Variable in colour
9.2	Important health, safety and environmental information:		
	pH value	:	N.D.
	Boiling point/boiling range	:	N.D. °C
	Flashpoint	:	N.D. °C
	Explosion limits	:	N.D. vol%
	Vapour pressure (at 20°C)	:	N.D. hPa
	Vapour pressure (at 50°C)	:	N.D. hPa
	Relative density (at 20°C)	:	1.7
	Water solubility	:	insoluble
	Soluble	:	No data available
	Relative vapour density	:	N.D.
	Viscosity (at 20°C)	:	72 Pa.s
	Partition coefficient n-octanol/water	:	N.D.
	Evaporation rate		
	ratio butylacetate	:	N.D.
	ratio to ether	:	N.D.
9.3	Other information:		
	Melting point/melting range	:	N.D. °C
	Auto-ignition point	:	N.D. °C
	Saturation concentration	:	N.D. g/m ³

10. Stability and reactivity

10.1 Conditions to avoid/reactivity:

- Stable under normal conditions

10.2 Materials to avoid:

- Heat sources, water/moisture

10.3 Hazardous decomposition products:

- On burning: release of carbon monoxide, carbon dioxide and formation of small quantities of nitrous vapours

11. Toxicological information

11.1 Acute toxicity:

TRIMETHOXYVINYL SILANE:

LD50 oral rat	: 7120	mg/kg
LD50 dermal rat	: N.D.	mg/kg
LD50 dermal rabbit	: 3434	mg/kg
LC50 inhalation rat	: 16	mg/l/4 h
LC50 inhalation rat	: 2714	ppm/4 h

11.2 Chronic toxicity:

EC carc. cat.	: not listed
EC muta. cat.	: not listed
EC repr. cat.	: not listed
Carcinogenicity (TLV)	: not listed
Carcinogenicity (MAC)	: not listed
Carcinogenicity (VME)	: not listed
Carcinogenicity (GWBB)	: not listed
Carcinogenicity (MAK)	: not listed
Mutagenicity (MAK)	: not listed
Teratogenicity (MAK)	: not listed
IARC classification	: not listed

11.3 Routes of exposure: ingestion, inhalation, eye and skin

11.4 Acute effects/symptoms:

AFTER INGESTION:

AFTER ABSORPTION OF HIGH QUANTITIES:

- Gastrointestinal complaints

AFTER EYE CONTACT:

- Slight irritation

11.5 Chronic effects:

- Not listed in carcinogenicity class (IARC,EC,TLV,MAK)
- Not listed in mutagenicity class (EC,MAK)
- Not classified as toxic to reproduction (EC)

12. Ecological information

12.1 Ecotoxicity:

TRIMETHOXYVINYL SILANE:

- LC50 (96 h): ≥ 100 mg/l (BRACHYDANIO RERIO)
- EC50 (48 h): 168.7 mg/l (DAPHNIA MAGNA)

12.2 Mobility:

- Volatile organic compounds (VOC): 2%
- Insoluble in water
- Substance sinks in water

- For other physicochemical properties see section 9

12.3 Persistence and degradability:

- | | | | |
|----------------------|---|------------------------|--------|
| - biodegradation BOD | : | N.D. | % ThOD |
| - water | : | No data available | |
| - soil | : | T $\frac{1}{2}$: N.D. | days |

12.4 Bioaccumulative potential:

- | | | |
|-----------------------|---|------|
| - log P _{ow} | : | N.D. |
| - BCF | : | N.D. |

12.5 Other adverse effects:

- WGK : 1 (Classification based on the components as per Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)
- Effect on the ozone layer : Not dangerous for the ozone layer (1999/45/EC)
- Greenhouse effect : no data available
- Effect on waste water purification : no data available

13. Disposal considerations

13.1 Provisions relating to waste:

- Waste material code (75/442/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 08 04 10 (waste adhesives and sealants other than those mentioned in 08 04 09)

13.2 Disposal methods:

- Remove to an authorized dump (Class II)

13.3 Packaging:

- Waste material code packaging (75/442/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15 01 02 (plastic packaging)

14. Transport information

- 14.1 Classification of the substance in compliance with UN Recommendations
UN-number : -
CLASS : NOT SUBJECT
SUB RISKS :
PACKING :
PROPER SHIPPING NAME :
- 14.2 ADR (transport by road)
CLASS : NOT SUBJECT
PACKING :
DANGER LABEL TANKS :
DANGER LABEL PACKAGES :
- 14.3 RID (transport by rail)
CLASS : NOT SUBJECT
PACKING :
DANGER LABEL TANKS :
DANGER LABEL PACKAGES :
- 14.4 ADNR (transport by inland waterways)
CLASS : NOT SUBJECT
PACKING :
DANGER LABEL TANKS :
DANGER LABEL PACKAGES :
- 14.5 IMDG (maritime transport)
CLASS : NOT SUBJECT
SUB RISKS :
PACKING :
MFAG :
EMS :
MARINE POLLUTANT :
- 14.6 ICAO (air transport)
CLASS : NOT SUBJECT
SUB RISKS :
PACKING :
PACKING INSTRUCTIONS PASSENGER AIRCRAFT :
PACKING INSTRUCTIONS CARGO AIRCRAFT :
- 14.7 Special precautions in connection with transport : not restricted for any mode of international transport

15. Regulatory information

15.1 EU legislation:

Not classified as dangerous in compliance with Directive 67/548/EEC and/or Directive 1999/45/EC

LABELLING NOT REQUIRED ACCORDING TO AVAILABLE INFORMATION

15.2 National provisions:

The Netherlands:
Waterbezwaarlijkheid: 11

Germany:
WGK : 1 (Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)

16. Other information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE
N.D. = NOT DETERMINED
***** = INTERNAL CLASSIFICATION

Exposure limits:

TLV : Threshold Limit Value - ACGIH US
OES : Occupational Exposure Standards - United Kingdom
MEL : Maximum Exposure Limits - United Kingdom
MAK : Maximale Arbeitsplatzkonzentrationen - Germany
TRK : Technische Richtkonzentrationen - Germany
MAC : Maximale aanvaarde concentratie - the Netherlands
VME : Valeurs limites de Moyenne d'Exposition - France
VLE : Valeurs limites d'Exposition à court terme - France
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium
GWK : Grenswaarde kortstondige blootstelling - Belgium
EC : Indicative occupational exposure limit values - directive 2000/39/EC

I : Inhalable fraction = **T** : Total dust = **E** : Einatembarer Aerosolanteil
R : Respirable fraction = **A** : Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit

a: aerosol		r: rook/Rauch	(fume)
d: damp	(vapour)	st: stof/Staub	(dust)
du: dust		ve: vezel	(fibre)
fa: Faser	(fibre)	va: vapour	
fi: fibre		om: oil mist	
fu: fume		on: olienevel/Ölnebel	(oil mist)
p: poussière	(dust)	part: particles	

Chronic toxicity:

K : List of the carcinogenic substances and processes - the Netherlands 2002

Full text of any R-phrases referred to under heading 2:

R10 : Flammable
R20 : Harmful by inhalation
R36/38 : Irritating to eyes and skin
R48/22 : Harmful: danger of serious damage to health by prolonged exposure if swallowed
R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65 : Harmful: may cause lung damage if swallowed